CBRN GAS MASKS

K11

CBRN Gas Mask — Panoramic

CE EN136:1998+AC:2003 · Anti-riot

MODEL · K11



OVERVIEW

Highest level of protection and visibility with a panoramic, non-fogging visor.

With its panoramic visor, non-fogging construction and two-sided filter connection, the K11 offers the highest level of protection and visibility in the most hazardous conditions. K11 is designed for comfort and ease of use, with a 6-point head harness for perfect tightness and a built-in voice diaphragm for easy communication. A vision correction kit accepts precision lenses, and a self-locking high-flow hydration system keeps the wearer hydrated in high-intensity operations.

85%	L / R	580 g
field of vision (EN136)	interchangeable canister side	without canister

FUNCTIONS / FEATURES

06 FEATURES

01

Interchangeable Canister

Mounts on either the left or right side of the face-piece to suit the user's physical condition and operational preference. NATO-standard DIN 40 thread; quick field replacement.

02

Hard-coated Panoramic Visor

Polycarbonate visor with hard coating for maximum field of vision.

03

Detachable Inner Mask

Non-fogging construction, easy cleaning and quick maintenance. Field-replaceable for continuous operations.

04

Built-in Voice Diaphragm

Clear short-distance communication with no external devices and no compromise of the seal.

05

Quick-Release 6-Point Harness

Airtight seal and fit, rapid donning/doffing, even pressure distribution and helmet compatibility.

06

Hydration, Communication & Vision Correction

Lever-operated self-locking hydration system, communication module and vision-correction module.

Specifications are subject to change without prior notice for product improvement. Values are typical and based on manufacturer and certification test data. · Rev. 2026-10

K11 CBRN Gas Mask — Panoramic

SPECIFICATION

K11

TECHNICAL SPECIFICATIONS

Mask material	Butyl rubber
Visor	Polycarbonate with hard coating
Weight	**580** g (without canister)
Field of vision	**85**% (EN136)
Available sizes	Standard (one size fits most)
Certification	CE (EN 136:1998 + AC:2003)

BREATHING RESISTANCE — FACE-PIECE

Airflow	30 L/min	95 L/min	160 L/min
Inhalation	**30** Pa	**90** Pa	**190** Pa
Exhalation	—	—	**260** Pa

PRODUCT DETAILS

05 VIEWS



02 Hard-coated Panoramic Visor



03 Detachable Inner Mask



04 Built-in Voice Diaphragm



05 Quick-Release 6-Point Harness



06 Hydration, Communication & Vision Correction

Specifications are subject to change without prior notice for product improvement. Values are typical and based on manufacturer and certification test data. · Rev. 2026-10